


Attorney cket No.: 12732-016001 / US4359

REMARKS

Claims 1-30 are pending in this application with claims 1-3 being independent. Claims 1-10 have been amended and claims 11-30 have been added. Support for claims 11-30 is found in claims 1-10 as filed. The specification and the abstract have been amended to conform to U.S. practice. No new matter is added.

Attached is a marked-up version of the changes being made by the current amendment.

Applicant asks that all claims be examined. Please apply any charges or credits to Deposit Account No. 06-1050.

Respectfully submitted,

Date:

Date: October 30, 2001

William Hare

William D. Hare
Reg. No. 44,739

Fish & Richardson P.C.
601 Thirteenth Street, NW
Washington, DC 20005
Telephone: (202) 783-5070
Facsimile: (202) 783-2331

SECRET

A

Version with markings to show changes made

In the specification:

The text at page 1, lines 1-4 has been canceled.

The claims extending between page 1, line 5 and page 3, line 10 have been moved and amended as described below.

Paragraph [0001] has been amended as follows:

[] Technical Field [to which the Invention belongs]

The present invention relates to an EL (electroluminescence) display device and an electronic device using the display device, and more specifically, relates to a technique for preventing deterioration of an EL element.

Please amend the specification beginning at page 3, line 18 and continuing forward as follows:

Paragraph [0002] has been amended as follows:

[[Prior Art]]

In recent years, development of a display device using an EL element as a self-light emitting element that utilizes an EL phenomenon of an organic material (EL display device) is being progressed. The EL display device is a self-light emitting type, and thus, does not need a back light unlike a liquid crystal display device. Further, the EL display device has a wide viewing angle, and therefore, is promising as a display portion of a portable device used outdoors.

Paragraph [0004] has been amended as follows:

[[Problems to be solved by the Invention]] Summary

In one general aspect, an EL display device includes a substrate on which an EL element is formed, a cover member, a filler for adhering said substrate on which the EL element is formed to said cover member, a sealing member for covering a side surface of said filler, and a frame member adhered with said sealing member.

In another general aspect, an EL display device includes an active matrix substrate on which a TFT and an EL element electrically connected with the TFT are formed, a cover member, a filler for adhering said active matrix substrate to said cover member, a sealing member for covering a side surface of said filler, and a frame member adhered with said sealing member.

In another general aspect, an EL display device includes a substrate on which an EL element composed of an anode arranged in a stripe, a cathode arranged in a stripe so as to be perpendicular to said anode, and an EL layer formed between said anode and said cathode, a cover member, a filler for adhering said substrate on which the EL element is formed to said cover member, a sealing member for covering a side surface of said filler, and a frame member adhered with said sealing member.

Implementations of the EL display devices may include one or more the following features. For example, the EL display devices may include a drying agent in the filler. The drying agent may include barium oxide. The drying agent may have a granular shape with an average diameter of 100 μmØ, and a density of 1 x 10² to 1 x 10⁵ atoms/cm³. The cover member may be provided with a light shielding film or color filter. An electronic device and/or a portable telephone may include the EL display devices in a display portion thereof.

An object of the present invention is to provide an EL display device with high reliability. Further, another object of the present invention is to provide an electronic device using such an EL display device with high reliability as its display portion.

Description of the Drawings

Fig. 1A is a side view of an EL display device without a sealing structure.

Fig. 1B is a side view of the EL display device of Fig. 1B with a sealing structure.

Fig. 2A is a cross-sectional side view of the EL display device of Fig. 1B taken along section lines A-A'

Fig. 2B is a cross-sectional side view of the EL display device of Fig. 1B taken along section lines B-B'.

Fig. 3 is a cross-section side view of an EL display device.

Fig. 4 is a plan view of a bonding apparatus of a double vacuum system.

093426 "H03005"

A

Fig. 5 is a cross-sectional side view of an EL display device in which a PVF film is used as a cover member.

Fig. 6 is a cross-sectional side view of a simple matrix EL display device having a cover member.

Fig. 7 is a cross-sectional side view of a simple matrix EL display device.

Fig. 8A is a perspective view of an EL display.

Fig. 8B is a perspective view of an EL display implemented in a video camera.

Fig. 8C is a perspective view of an EL display implemented as a head mounted display.

Fig. 8D is a perspective view of an EL display implemented in a DVD playback device.

Fig. 8E is a perspective view of an EL display implemented in a device with a camera and a display portion.

Fig. 8F is a perspective view of an EL display implemented in a portable computer.

Fig. 9A is a perspective view of a portable telephone in which the EL display has been incorporated.

Fig. 9B is a perspective view of a car audio system in which the EL display has been incorporated.

Paragraph [0005] has been amended as follows:

[[Means to solve the Problem]] Detailed Description

A structure of the present invention is explained with reference to Fig. 1. Fig. 1A shows an EL display device of the present invention in a state that a sealing structure for sealing an EL element in a sealing space is not provided.

Paragraph [0022] has been amended as follows:

[[Embodiment Mode of the Invention]]

Embodiment mode of the present invention is explained with reference to Fig. 3. Fig. 3 is a cross-sectional view of an EL display device of the present invention. Note that the basic structure is the same as Fig. 2A, and thus, the explanation is made as the need arises.

Paragraph [0037] has been amended as follows:

[[[]Embodiments[]]]

[[Embodiment 1]]

A

In this embodiment, an example of using a PVF film as a cover member is shown in Fig. 5. In Fig. 5, reference numeral 501 indicates a light transmitting substrate (a plastic substrate in this embodiment), 502 indicates a pixel portion, 503 indicates a driver circuit, and the respective portions are formed of TFTs. Besides, an EL element 504 is formed in the pixel portion 502, and image display is performed.

Paragraph [0040] has been amended as follows:

[[[Embodiment 2]]]

In this embodiment, an example of implementing the present invention in a simple matrix EL display device is shown in Fig. 6. In Fig. 6, reference numeral 601 indicates a plastic substrate, and reference numeral 602 indicates a cathode with a lamination structure of an aluminum film and a lithium fluoride film (the lithium fluoride film corresponds to the portion contacting an EL layer). In this embodiment, the cathode 602 is formed by an evaporation method. Note that, although not shown in Fig. 6, a plurality of cathodes is [are] arranged in stripe in a direction perpendicular to the paper.

Paragraph [0048] has been amended as follows:

[[[Embodiment 3]]]

In this embodiment, an example of implementing the present invention in a simple matrix EL display device is shown in Fig. 7. In Fig. 7, reference numeral 701 indicates a glass substrate, and reference numeral 702 indicates an anode made of a transparent conductive film. In this embodiment, a compound of indium oxide and tin oxide is formed by a sputtering method. Note that, although not shown in Fig. 7, a plurality of anodes is [are] arranged in stripe in a direction perpendicular to the paper.

Paragraph [0055] has been amended as follows:

[[[Embodiment 4]]]

An EL display device formed by implementing the present invention is of a self light emitting type, and thus, it is excellent in visibility in the light in comparison with a liquid crystal display device, and also has a wide viewing angle. Therefore, the EL display device can be used as a display portion of various electronic devices. For example, the EL display device of the present invention may be used as a display portion of an EL display (a display incorporated with

100E01-924E3460

the EL display device in its casing) having a screen size of a 30 inch diagonal or larger (typically a 40 inch diagonal or larger) in order to watch TV broadcasting and the like with a large screen.

Paragraph [0070] has been amended as follows:

[[Effects of the Invention]]

The deterioration of the EL element portion of the EL display device can be effectively suppressed by implementing the present invention. Therefore, the EL display device with high reliability can be obtained. Further, such an EL display device with high reliability is used as the display portion of the electronic device, whereby the reliability of the electronic device can be enhanced.

[[Brief Description of the Drawings]]

[Figs. 1] Diagrams showing top surface structures of an EL display device.

[Figs. 2] Diagrams showing cross sectional structures of the EL display device.

[Fig. 3] A diagram showing a cross sectional structure of an EL display device.

[Fig. 4] A diagram showing a bonding apparatus of a double vacuum system.

[Fig. 5] A diagram showing a cross sectional structure of an EL display device.

[Fig. 6] A diagram showing a cross sectional structure of an EL display device.

[Fig. 7] A diagram showing a cross sectional structure of an EL display device.

[Figs. 8] Diagrams showing specific examples of electronic devices.

[Figs. 9] Diagram showing specific examples of electronic devices.]

In the claims:

Claims 1-10 have been amended as follows:

[[Claim 1]]

1. An EL display device **[characterized by]** comprising a substrate on which an EL element is formed, a cover member, a filler for adhering said substrate on which the EL element

09783426-103001
F00001-02 FEB 2001

A

is formed to said cover member, a sealing member for covering a side surface of said filler, and a frame member adhered with said sealing member.

[[Claim 2]]

2. An EL display device **[characterized by]** comprising an active matrix substrate on which a TFT and an EL element electrically connected with the TFT are formed, a cover member, a filler for adhering said active matrix substrate to said cover member, a sealing member for covering a side surface of said filler, and a frame member adhered with said sealing member.

[[Claim 3]]

3. An EL display device **[characterized by]** comprising a substrate on which an EL element composed of an anode arranged in a stripe, a cathode arranged in a stripe so as to be perpendicular to said anode, and an EL layer formed between said anode and said cathode, **[is formed,]** a cover member, a filler for adhering said substrate on which the EL element is formed ☐ said cover member, a sealing member for covering a side surface of said filler, and a frame member adhered with said sealing member.

[[Claim 4]]

4. An EL display device as claimed in claim 1 wherein **[any one of claims 1 to 3, characterized in that]** a drying agent is included in said filler.

[[Claim 5]]

5. An EL display device as claimed in claim 1 wherein **[any one of claims 1 to 3, characterized in that]** said cover member is provided with a light shielding film or color filter.

[[Claim 6]]

6. An EL display device as claimed in claim 5 wherein **[, characterized in that]** a drying agent is included in said light shielding film or color filter.

FOOT-9243/60

A

[[Claim 7]]

7. An EL display device as claimed in claim 4 wherein [or claim 6, characterized in that] said drying agent [is] comprises barium oxide.

[[Claim 8]]

8. An EL display device as claimed in claim 4 wherein [or claim 6, characterized in that] said drying agent has a granular shape with an average diameter of 100 $\mu\text{m}\varnothing$, and is included with a density of 1×10^2 to 1×10^5 atoms/cm³.

[[Claim 9]]

9. An electronic device including **[characterized by using]** the EL display device according to claim 1 **[any one of claims 1 to 8]** in a display portion thereof.

[[Claim 10]]

10. A portable telephone including **[characterized by using]** the EL display device according to claim 1 **[any one of claims 1 to 8]** in a display portion thereof.

In the abstract

The abstract has been amended as follows:

[[Document Name] Abstract

[[Summary]

[Problem] To provide an EL display device with high reliability

[Solving Means]]

A cover member [107] is adhered onto a substrate [101] on which an EL element is formed with a filler [208] as an adhesive. Further, a sealing member [209] is provided so as to cover a side surface (an exposing surface) of the filler [208], and a frame member [108] is adhered using the sealing member [209]. With this structure, the EL element is completely sealed by the filler [208], and shut from moisture and the like from the outside. Thus, deterioration of an EL layer due to oxidization can be prevented.

[[Selected Drawing] Fig. 2

[DESCRIPTION OF A MARK]

[Fig. 2]

102

A pixel portion

100-443887-100

A

103 A driver circuit

B indicates "a light radiation direction"

[Fig. 3]

302 A pixel portion

303 A driver circuit

Y indicates "a light radiation direction"

[Fig. 5]

502 A pixel portion

503 A driver circuit

B indicates "a light radiation direction"

[Fig. 6]

Y indicates "a light radiation direction"

[Fig. 7]

B indicates "a light radiation direction"

[Fig. 8]

(A) 2001 A casing

2002 A support stand

2003 A display portion

(B) 2101 A main body

2102 A display portion

2103 A sound input portion

2104 Operation switches

2105 A battery

2106 An image receiving portion

(C) 2201 A main body

2202 Signal cables

2203 A head fixing band

2204 A display portion

2205 An optical system

2206 An EL display device

(D) 2301 A main body

2302 A recording medium

2303 Operation switches

2304 A display portion (a)

2305 A display portion (b)

(E) 2401 A main body

2402 A camera portion

2403 An image receiving portion

2404 An operation switch

2405 A display portion

(F) 2501 A main body

2502 A casing

2503 A display portion

2504 A keyboard

FIG. 10

A

Applicant : Shunpei YAMAZAKI et al.
Serial No. : 09/783,426
Filed : February 15, 2001
Page : 19

Attorney [REDACTED]cket No.: 12732-016001 / US4359

[Fig.9]

(A)

2602

2603

2604

2605

2606

(B)

2702

2703

2704

2601 A main body

A sound input portion

A sound input portion

A display portion

Operation switches

An antenna

2701 A main body

A display portion

Operation switches

Operation switches]

FIG. 9

A